



PAINT PROTECTION KITS AFTER CARE INSTRUCTIONS

Thank you for purchasing paint protection from Paintshield Ltd. We would like to draw your attention to the following after care instructions:

1. Your car should not be washed with any car wash detergent for 7 days after installation, allowing time for the film to cure properly on the car otherwise edge lift may occur which is not repairable.
2. Slight milkiness, patchiness or bubbles may occur, this is nothing to be concerned over as it is a natural part of the drying out process and is purely the result of trapped moisture under the film which will dissipate. This can take up to 3 weeks to completely disappear (depending on humidity levels).
3. Looking after your protective film is quite straightforward, you should use a regular car shampoo and can (and should) wax the product in the usual manner.
4. If jet washing the product you **MUST** keep the nozzle at least 3 feet from the edge of the film, as the sheer force of water may cause it to lift. Should this occur take the product immediately to your certified installer. (do not touch it) who will endeavour to correct the situation)
5. It is advisable to remove any bird droppings from the film as quickly as possible as the acid content of the droppings may have a detrimental effect on the film over time.
6. Do not use abrasive chemicals or paint restoration products on the film of any kind.
7. Products such as t-cut or other harsh refinishing products will damage the protective coating and cause an adverse reaction, they should be kept away from the product at all costs. The same is true of degreasers.
8. Similarly bleaches and other heavy cleaning chemicals may cause problems and should be avoided.
9. Petrol, diesel, oil, etc causes no problems to the film whatsoever.
10. Under no circumstances should petroleum distillate products be used on ANY paint protection Film.



PAINT PROTECTION KITS AFTER CARE INSTRUCTIONS

11. Under no circumstances should Traffic Film removers, TFR's (truck wash) or Autosmart G101 be used on ANY paint protection film

Please see warranty for full details.